architectural hardware BAUHAUS LOW PROFILE EURO PROFILE LOCK HANDLE PAIRED VIEW 55 Φ This lock handle is suitable for use with most U.K. Euro Profile cylinders and sashlocks with a 48mm CTC. **EURO PROFILE SASHLOCKS** (not Included, must be ordered seperately) Iron starter screw x 1pc. Drill pilot holes, use the starter screw to cut a thread Spindle: 7.8mm x 68mm - 1pc. YKCSLE27.CE 2.1/2" PVD Brass Finish YKCSLE28.CE 2.1/2" PSS YKCSLE29.CE 2.1/2" SSS YKCSLE37.CE 3" PVD Brass Finish YKCSLE38.CE 3" PSS YKCSLE39.CE 3" 8x Brass wood Screw Fasten the Brass Screw into the Pilot hole 2.5 mm Allen key: Used to fasten handle

3 4 1x 68mm spindle Box Pair of 1x Allen 8x Brass suitable for 35mm & 1x Iron screw Contains lever handles 45mm thick door wood screws

M Marcus Ltd., Dudley

Product Code	Material
BAU7348	Solid Brass

Available in all Heritage Brass finishes.

Sizes shown are in mm and approximate. We reserve the right to amend where necessary and without any prior notice.