## architectural hardware TRIDENT LEVER LATCH HANDLE PAIRED VIEW 55 50 This latch handle is suitable for use with most U.K. tubular latches. For a new door installation we would recommend using our York standard tubular latch from the list below. TUBULAR LATCH (not Included, must be ordered seperately) Iron starter screw x 1pc. $2^{1/2}$ " Antique Finish Drill pilot holes, use the starter screw to cut a thread YKTL2-AT 2<sup>1/2</sup>" Black Finish YKTL2-BLK 21/2" Matt Bronze Finish YKTL2-MB 21/2" Brass Finish YKTL2-PB YKTL2-PC&PN 21/2" Polished Chrome & Nickel Finish $2^{1/2}$ " Satin Brass Finish YKTL2-SB 8x Brass wood Screw $2^{\scriptscriptstyle 1/2}{}''$ Satin Nickel & Chrome Finish YKTL2-SN&SC Fasten the Brass Screw into the Pilot hole Spindle: 7.8mm x 68mm - 1pc. 3" Antique Finish YKTL3-AT 3" Black Finish YKTL3-BLK 3" Matt Bronze Finish YKTL3-MB YKTL3-PB 3" Brass Finish YKTL3-PC&PN 3" Polished Chrome & Nickel Finish YKTL3-SB 3" Satin Brass Finish (1)4 ③ YKTL3-SN&SC 3" Satin Nickel & Chrome Finish 1x 68mm spindle Box Pair of lever handles suitable for 35mm & 1x Iron screw 8x Brass Contains wood screws 45mm thick door M Marcus Ltd., Dudley

Product Code	Material
TRI1310	Solid Brass

Available in all Heritage Brass finishes.

Sizes shown are in mm and approximate. We reserve the right to amend where necessary and without any prior notice.